



ORMESA®
• MADE IN ITALY SINCE 1980 •

DONDOLINO



DONDOLINO

Stability in motion.

Dondolino is a prone standing frame designed and built by Ormesa to help children acquire **independence in maintaining a standing posture**.

Dondolino's use in everyday contexts **encourages environmental interaction** by facilitating upper limbs and head mobility and the development of individual motor skills.

Dondolino is an extremely versatile device that comes in three sizes with a wide range of adjustments. It can be used by children and teens from 75 to 150 cm tall, **adapting to their growth, to their development of individual skills and to their needs of hip and knee flexions**.



PRODUCT
MARKED **CE**

DONDOLINO is a MEDICAL DEVICE that COMPLIES WITH THE SAFETY REQUIREMENTS defined with the REGULATION (EU) 2017/745





Tilting frame

Through spring stopper adjuster it is possible to switch from the upright position to a more prone one in order to stimulate the active control of head and trunk.

These changes of attitude can be applied in a completely fluid way even with the child inside the standing frame, without causing pathological reactions of postural discomfort.

Dondolino contains without forcing, adapting the structure to different postural needs.



**Technical features
and adjustments**



Frame

for children needing to improve straightening reactions. Without ledges to guarantee safety. It allows trunk rotation and maximum freedom of movement of the upper limbs. Smooth continuous adjustment (through spring stopper adjuster).



Tools free

adjustments without tools but with special knobs, designed by Ormesa, with effective and safe grip. The knobs effectively maintain the tightening thanks to an internal mechanism that does not mark and ruin the tube.




Graduated bars


to help finding the right postural setting chosen by the therapist.



Pelvic support and thoracic support




independently adjustable in circumference, height and forward-backward. If the user has sufficient trunk control, the thoracic support can be removed.






Birch plywood table

designed for educational purposes and for supporting upper limbs, it can be removed to facilitate upper limb and trunk exercises. Height, inclination and forward-backward adjustment.





Knee pads

with removable, washable padding and with holes for patella discharge. Independently adjustable in height, rotation, abduction and forward-backward.



Heel stops

width and depth adjustments.



Birch plywood footrest

height adjustments.




Twin swivel wheels

75 mm diameter, all with brakes. The wheels allow movement from one room to another, even during use.




1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30
31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50
51	52	53	54	55	56	57	58	59	60
61	62	63	64	65	66	67	68	69	70
71	72	73	74	75	76	77	78	79	80
81	82	83	84	85	86	87	88	89	90
91	92	93	94	95	96	97	98	99	100

Components



944 Circumference reducers

3 cm thick each. They can be inserted into the supports for thinner users.



865 Multiadjustable headrest


height, inclination and forward-backward adjustment with knobs.





Dondolino sizes and weight


	size 1	size 2	size 3
A: base encumbrance	63 cm	77 cm	83 cm
B: length encumbrance	from 75 to 85 cm	from 81 to 91 cm	from 85 to 95 cm
C: footrest to table height	from 45 to 79 cm	from 52 to 90 cm	from 62 to 107 cm
D: width encumbrance	63 cm	67 cm	71 cm
E: footrest to knee pads height	from 12 to 26 cm	from 12 to 36 cm	from 14 to 48 cm
F: footrest to pelvic support height	from 39 to 59 cm	from 47 to 74 cm	from 58 to 93 cm
G: footrest to thoracic support height	from 51 to 76 cm	from 56 to 90 cm	from 70 to 110 cm
L: circumference of supports	60 cm	65 cm	70 cm
M: user height	from 75 to 100 cm	from 90 to 125 cm	from 120 to 150 cm
P: frame inclination	from 0° to 19°	from 0° to 14°	from 0° to 11°
Total weight	21 kg	24 kg	26 kg
Maximum load	35 kg	45 kg	55 kg



Make sure that measures F and G indicated in the figure do not exceed the suggested range indicated for the supports.

Pietro and his story await you in the Ormesa official website, together with other protagonists of our fantastic global community.





A special thanks to the families who participated with enthusiasm in our project. It is thanks to our customers and their stories that we find the energy and stimuli to evolve day by day.

CE complies with MDR (EU) 2017/745

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= **ISO 13485** =

Ormesa srl - Via A. Da Sangallo, 1 | 06034 Foligno (PG) - ITALY
Tel. +39 0742 22927 | FAX +39 0742 22637 | info@ormesa.com

www.ormesa.com